The procedure for upgrading the PFXi firmware to V4.60 is as follows:

- 1. Connect the PFXi to the source computer (laptop of PC) via USB.
- 2. Switch on the PFXi whilst holding down the 'F1' on the instrument. A dialog will appear on the LCD screen with the text 'Enter Function No'
- 3. Enter '8192' and press enter 🖵 on the instrument keypad. The 'Firmware Upgrade' screen will appear with the message 'Waiting For Host....'
- 4. Start the PFXi Flash loader software on the PC :

蹦 PFXi Flash Lo	oade	r						
Connect								
Instrument Type :								
Serial No :								
MAC Address :	00	1B	7B	ff	ff	ff		
Flash Program —								
Load File	Load File Dx00000000							
Program	High Flash Address 0x00000000							
\\/siting								
Waiting								

The green status bar indicates that the software is successfully communication with the instrument.

5. Click on the 'Connect' button and confirm the instrument type and serial number are correct.

翊 PFXi Flash Loader								
Connect								
Instrument Type :	PFX	i 995						
Serial No :	5432	21						
MAC Address :	00	1B	7B	0	0	1]	
Flash Program —								
Load File	Low Flash Address 0x00000000							
Program	High Flash Address 0x00000000							
Waiting								

6. Click on the 'Load File' button and navigate to the new flash file ("PFXi_4_50_rel.flash"). The file will take a few seconds to load. When the file has loaded correctly the 'Program' button will be enabled and the 'high' address of the firmware displayed (this is for information only):

蹦 PFXi Flash Lo	oade	r							
Connect									
Instrument Type :	PFXi	995							
Serial No :	5432	21							
MAC Address :	00	1B	7B	0	0	1			
MAC Address : 00 TB 7B 0 0 T Flash Program Load File 0x00000000 Program 0x00126800									
Waiting									

7. Click on the 'Program' button. The new firmware is then downloaded and programmed into the instrument.

NOTE:

DO NOT switch off or press any buttons on the instrument or the Flash Loader software until programming is complete. Failure to do so may render the instrument inoperable.

8. The Flash Loader software will indicate progress and instrument state during programming:

🕮 PFXi Flash Loader								
Connect								
Instrument Type :	PFXi	995						
Serial No :	54321							
MAC Address :	00	1B	7B	0	0	1		
Flash Program				v Fla:	sh Ad	dress		
Program	High Flash Address 0x00126800							
Sending 651 of 1508								
Waiting								

- When programming is complete, the LCD screen will display 'Restart Instrument Update Successful'
 – Turn off instrument power and restart. Confirm that the software version is correct on the instrument
 splash screen (it should be V4.60).
- 10. Repeat the whole process from step 1, selecting "PFXiFlashMapVerX1.flash" as the flash file.